

B2  
--The present invention relates to an optical apparatus having a function of correcting image shaking caused by changes in the relative angles of an object to be photographed and the optical apparatus.--

Please substitute the paragraph starting at page 2, line 8 and ending at page 2, line 22 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

B3  
--Optical apparatuses of the kind arranged to be capable of correcting image shaking have heretofore been developed in varied manners. Fig. 7 shows an example of such optical apparatuses. In the case of the optical apparatus shown in Fig. 7, the so-called variable angle prism 100 is arranged in front of an optical system composed of lens units 101 to 104 and a diaphragm 105 to correct image shaking before a light flux P from an object comes to be incident on the optical system. Referring to Fig. 7, the lens units 101 to 104 and the diaphragm 105 are supported by a fixed tube 105. An image sensor 107 is arranged to convert into an electrical signal an optical image formed on a focal plane that is located in rear of the fixed tube 106.--

Please substitute the paragraph starting at page 3, line 2 and ending at page 3, line 20 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

B4  
--In view of the above problem, some known optical apparatuses have been developed to permit reduction in size. For example, an optical apparatus is arranged to have the variable angle prism disposed between two lens units within an optical system composed of a plurality of lens units. Another optical apparatus, which is of the type

B4  
cont

called a lens shift type, is arranged to correct image shaking by moving some of a plurality of lens units in a direction perpendicular to an optical axis. Some other optical apparatus have been developed to have an electronic image-shake correcting function called an electronic image stabilizing device, which corrects image shaking in the following manner. A CCD, which has a larger area than an actually necessary area as an image sensor (thus requiring use of a large optical system having an image circle covering the whole surface of the CCD), is arranged to correct image shaking by varying the reading position thereof according to information on detected image shaking.--.

---

Please substitute the paragraph starting at page 4, line 10 and ending at page 4, line 21 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

---

B5  
cont

--In the case of the above-stated function of optically correcting image shaking by deflecting a light flux within the optical system, if the optical apparatus is arranged to correct the image shaking in such a way as to have an object image not moving on the image forming plane at the time of a change of relative angles of the object and the optical apparatus, the vignetting degree of the light flux at each point of an object image on the image forming plane would vary to change the light quantity distribution of the object image, as the relative angles of the object and the optical apparatus have changed.--.

Please substitute the paragraph starting at page 4, line 22 and ending at page 5, line 12 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

BS  
CMT

--Such a state is explained with reference to Fig. 9. In Fig. 9, image forming positions are shown on the abscissa axis and the luminance of the image is shown on the ordinate axis. A one-dot-chain line shown in Fig. 9 represents the initial distribution of light quantity obtained before the relative angles of the object and the optical apparatus change. Full lines "a" and "b" shown in Fig. 9 represent light quantity distributions obtained with image shaking corrected when the relative angles change, for example, alternately to the right and to the left. When image shaking that actually takes place continuously are corrected in this manner, although the object image is corrected to be not moving on an image plane, the image-shake correction results in variations of luminance of the picture taking place in synchronism with the image shaking. The luminance variations become salient particularly in the peripheral part of the image plane. As a result, the quality of an image thus obtained degrades to an unacceptable degree.--.

Please substitute the paragraph starting at page 5, line 13 and ending at page 5, line 27 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--Further, the electronic image-shake correcting function also has a problem similar to that of the optical image-shake correcting function. In this case, the light quantity distribution on the image-forming plane does not change, since the relation between the image-forming plane 116 and the optical system, which is composed of the lens units 111 to 114 and the diaphragm 115 as shown in Fig. 8, is unchanging. However, when the object image is caused to move by the change in relative angles of the object and the optical apparatus, the reading position also changes following the movement of the object image, for example, as indicated by reading positions I and II in Fig. 10. The change of the

B5  
Cord

reading position then brings about the same phenomenon as in the case of the optical image-shake correcting function.--.

---

Please substitute the paragraph starting at page 6, line 2 and ending at page 6, line 12 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

---

B6

--The invention is directed to the solution of the problems with prior art described above. It is, therefore, an object of the invention to provide an optical apparatus arranged to be capable of giving an easily viewable image of high quality by alleviating luminance variations that occur in the peripheral parts of an image plane in correcting image shaking and by lessening a luminance difference between central and peripheral parts of the image plane, particularly at a part in the neighborhood of a telephoto end position where the variations of luminance become conspicuous.--.

---

Please substitute the paragraph starting at page 6, line 16 and ending at page 6, line 20 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

---

B7  
Cord

---(1) The full-open aperture diameter of a diaphragm provided for control over the quantity of a light flux passing through a variable magnification optical system having an image-shake correcting function is limited according to the focal length.--.

Please substitute the paragraph starting at page 6, line 21 and ending at page 6, line 25 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--(2) An on-axial light flux in the neighborhood of the telephoto end position of the variable magnification optical system, which takes therein an off-axial light flux as well, and the on-axial light flux is limited by a diaphragm.--.

*B7  
Cond* Please substitute the paragraph staring at page 6, line 26 and ending at page 6, line 28 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--(3) The on-axial light flux is limited by an auxiliary diaphragm that is disposed close to a main diaphragm arranged to determine an F-number.--.

Please substitute the paragraph staring at page 7, line 1 and ending at page 7, line 7 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--(4) The amount of shift of a lens unit to be shifted in a direction perpendicular to an optical axis is corrected according to information on the position of the variable-magnification optical system in such a way as to cancel a movement of an image caused by a tilt of the variable-magnification optical system by the shift of the lens unit.--.

Please substitute the paragraph staring at page 7, line 14 and ending at page 7, line 17 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

89 --Fig. 1 shows a state obtained at a telephoto end position of a variable-magnification optical system of an optical apparatus according to a first embodiment of the invention.--.

Please substitute the paragraph starting at page 7, line 18 and ending at page 7, line 21 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--Fig. 2 shows a state obtained at a wide-angle end position of the variable-magnification optical system of the optical apparatus according to the first embodiment of the invention.--.

Please substitute the paragraph starting at page 8, line 1 and ending at page 8, line 3 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

89 --Fig. 5 schematically shows the arrangement of an optical apparatus having an image-shake correcting function according to the invention.--.

Please substitute the paragraph starting at page 8, line 8 and ending at page 8, line 10 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

B10 --Fig. 7 is a longitudinal sectional view of the conventional optical apparatus having an image-shake correcting function.--.

Please substitute the paragraph starting at page 8, line 22 and ending at page 8, line 23 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

---

*B11* --Fig. 12 is an exploded perspective view showing a zoom-lens barrel shown in Fig. 11.--.

Please substitute the paragraph starting at page 8, line 24 and ending at page 8, line 26 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--Fig. 13 is an exploded perspective view of an image-shake correcting unit mounted on the zoom lens shown in Fig. 11.--.

---

Please substitute the paragraph starting at page 9, line 11 and ending at page 9, line 13 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

---

*B12* --Fig. 18 is a block diagram showing a system for image-shake correction control and diaphragm control arranged in the second embodiment.--.

---

Please substitute the paragraph starting at page 9, line 24 and ending at page 10, line 20 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

B13 --Figs. 1 and 2 show a variable magnification optical system having an image-shake correcting function according to a first embodiment of the invention. The variable-magnification optical system is composed of lens units 1 to 4 having positive, negative, positive and positive refracting powers, respectively. In Fig. 1, the variable-magnification optical system is shown in a state obtained with the optical system at a telephoto end position. Fig. 2 shows the variable-magnification optical system in a state obtained with the optical system at a wide-angle end position. The lens unit 1 is a fixed lens unit. The lens unit 2 is a variator lens unit, which is provided for varying the magnification of the optical system by moving backward and forward. The lens unit 3 is an image-shake correcting lens unit that is arranged to deflect a light flux by moving (shifting) in a direction perpendicular to an optical axis. The lens unit 4 is a focusing lens unit provided for adjusting the focus of the variable-magnification optical system by moving backward and forward. A diaphragm 5 is provided for limiting the quantity of a light flux passing through the optical system. A focal plane 6 is arranged to form thereon an image of a photo-taking object.--

Please substitute the paragraph starting at page 11, line 6 and ending at page 12, line 6 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

BH --In Fig. 3, the image forming positions are shown on the abscissa axis and the luminance of the image is shown on the ordinate axis. A full line "c" represents a light quantity distribution obtained on the focal plane 6 shown in Fig. 1. A two-dot-chain line "d" represents a light quantity distribution obtained when the diaphragm 5 is opened to a position where it does not block the on-axial light flux "a". A broken line "e" represents a light quantity distribution obtained when the diameter of the lens unit 1 is reduced to a size



at which only such a portion of the on-axial light flux that can pass through the full-open aperture of the diaphragm as shown in Fig. 1 is allowed to pass. In other words, with the lens unit 1 arranged to have a large diameter to receive the on- and off-axial light fluxes in large quantity, at least the on-axial light flux is made to be limited by the diaphragm 5. This arrangement is made such that a difference in luminance between the central and peripheral parts of the image plane is lessened. Fig. 4 shows variations of light-quantity distribution taking place with the image-shake correction actually performed. Lines or curves c', c'', d' and d'' show the variations of light-quantity distribution obtained with the diaphragm 5 at its positions where the lines "c" and "d" are obtained, respectively. Fig. 4 clearly shows that the variations taking place in the peripheral part of the image plane, in particular, is greatly improved by limiting the full-open aperture diameter of the diaphragm 5, as indicated by variations I and II of luminance.--.

2H  
CON

Please substitute the paragraph starting at page 12, line 7 and ending at page 12, line 16 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--Fig. 5 shows in outline the arrangement of the optical apparatus having the image-shake correcting function. For the lens units 1 to 4, the diaphragm 5 and the focal plane 6 shown in Fig. 1, the following parts are provided as shown in Fig. 5. A fixed tube 7 is arranged to hold the lens unit 1. A moving frame 8 is arranged to hold the lens unit 2 in a known bar-sleeve structure to be movable in the direction of the optical axis by a stepping motor through a known mechanism including a rack and a feed screw.--.

Please substitute the paragraph starting at page 12, line 17 and ending at page 12, line 24 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

*By  
concl*

--A shift frame 9 is arranged to hold the lens unit 3 and to be movable in a direction perpendicular to the optical axis O by a guide mechanism (not shown), which is arranged between a holding frame 10 and the shift frame 9. The position of the shift frame 9 is arranged to be determined in the directions of pitch and yaw by a driving means and a position detecting means which are not shown.--.

Please substitute the paragraph starting at page 12, line 25 and ending at page 13, line 7 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--A moving frame 11 is arranged to hold the lens unit 4 in a known bar-sleeve structure to be movable in the direction of the optical axis by a stepping motor through a known mechanism including a rack and a feed screw. A known diaphragm device 12 is arranged to support and drive the diaphragm 5. The diaphragm device 12 is preferably a so-called iris diaphragm that has a plurality of sickle-shaped diaphragm blades arranged in a circumferential direction so as to form an approximately circular aperture by rotating the plurality of diaphragm blades at the same time.--.

---

Please substitute the paragraph starting at page 13, line 14 and ending at page 14, line 12 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

BIS  
only

--A microcomputer 16 is arranged to control lens-driving actions. When a power supply is switched on, the microcomputer 16 causes a focus motor-driving circuit 19 and a zoom motor-driving circuit 20 to rotate their respective stepping motors for moving the moving frames 11 and 8 while continuously monitoring the output of a focus-reset circuit 17 and that of a zoom-reset circuit 18. The output of the focus-reset circuit 17 and that of the zoom-reset circuit 18 are inverted respectively when each of the moving frames 11 and 8 comes to a predetermined position, where light from a light emitting part of a photo-interrupter disposed at a fixed part is blocked, or allowed to pass at a boundary part, by a light blocking part of each moving frame. After that, with this position used as a datum position, the number of driving steps of each stepping motor is counted within the microcomputer 16 to find the absolute position of each of the lens units 4 and 2. Information on the focal length can be accurately obtained by this arrangement. A diaphragm-driving circuit 21 is provided for opening and closing the diaphragm 5 under the control of the microcomputer 16. The aperture of the diaphragm 5 is controlled on the basis of information B on luminance of the video signal taken in the microcomputer 16. Information on the diaphragm aperture thus obtained is detected by an aperture value detecting circuit 22 and is supplied to the microcomputer 16.--.

Please substitute the paragraph staring at page 14, line 13 and ending at page 14, line 23 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--By the aperture control operation, the full-open (maximum) aperture diameter of the diaphragm is limited according to the focal length to have some area where the diaphragm is not opened as indicated by a hatched part of Fig. 6, which shows the focal length on the abscissa axis and the full-aperture diameter of the diaphragm on the ordinate

axis. Under this aperture control, the difference in luminance between the central part and the peripheral part of the image plane can be kept small, particularly by cutting off the on-axial light flux on the side of the telephoto end position.--.

Please substitute the paragraph starting at page 14, line 24 and ending at page 15, line 8 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

BIS Cont  
--Although the structure of an optical system is generally arranged to have a smaller luminance difference between the central part and the peripheral part of an image plane in the telephoto end than in the wide-angle end, an image formed on an image forming plane is caused by one and the same image shake to move to a greater extent in proportion to the focal length in the telephoto end than in the wide-angle end. Therefore, the problem of luminance variations on the image plane caused by actual image shaking becomes more serious at the telephoto end than at the wide-angle end. This calls for some improvement in light-quantity distribution obtained in the neighborhood of the telephoto end of the lens system.--.

Please substitute the paragraph starting at page 15, line 9 and ending at page 15, line 18 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--The optical apparatus is provided with a pitch-angle (vertical slanting angle) detecting circuit 23 and a yaw-angle (horizontal slanting angle) detecting circuit 24. Each of these angles is detected by integrating the output of an angular velocity sensor which, for example, is a vibration gyro or the like secured to the optical apparatus. The outputs of the

two angle-detecting circuits 23 and 24, which show information on slanting angles of the optical apparatus, are supplied to the microcomputer 16.--.

Please substitute the paragraph starting at page 15, line 19 and ending at page 15, line 26 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

*B15 and*  
--For moving the lens unit 3 in correcting image shaking, the optical apparatus is provided with pitch (vertical) and yaw (horizontal) coil-driving circuits 25 and 26. Each of the pitch coil-driving circuit 25 and the yaw coil-driving circuit 26 is arranged to generate a driving force for the lens unit 3 by the so-called moving coil device in which a coil is disposed at a gap of a magnetic circuit having a magnet.--.

Please substitute the paragraph starting at page 15, line 27 and ending at page 16, line 10 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--A pitch (vertical) position-detecting circuit 27 and a yaw (horizontal) position-detecting circuit 28 are provided for detecting amounts of shift of the lens unit 3 with respect to the optical axis. Each of the circuits 27 and 28 is arranged, for example, to have a light-emitting element and a light-receiving element fixedly opposed to each other, to have a slit which is formed in the shift frame 9 interposed in between these light emitting and receiving elements, and to obtain a shift amount of the lens unit 3 as an electrical signal. The information on the amount of shift thus obtained is also supplied to the microcomputer 16.--.

Please substitute the paragraph starting at page 16, line 13 and ending at page 16, line 24 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

3/16  
cont

--When the lens unit 3 moves in a direction perpendicular to the optical axis, a light flux passing there is bent. As a result, the position of an object image formed on the CCD 13 moves. The microcomputer 16 then controls and causes the optical system to move the same amount as the movement amount of the image position actually caused by the slant of the optical apparatus in a direction opposite to the direction in which the object image moves. The image-shake correcting action thus can be carried on to keep the formed image unshakable even when the optical apparatus slants to shake the image.--.

Please substitute the paragraph starting at page 16, line 25 and ending at page 17, line 10 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--Within the microcomputer 16, shift-amount signals obtained from the pitch position-detecting circuit 27 and the yaw position-detecting circuit 28 indicating the shift amounts of the lens unit 3 are respectively subtracted from inclination signal obtained from the pitch-angle detecting circuit 23 and the yaw-angle detecting circuit 24 indicating the inclinations of the optical apparatus to obtain difference signals. Then, the pitch coil-driving circuit 25 and the yaw coil-driving circuit 26 are caused to drive the shift frame 9 according to the difference signals. Under this control, the lens unit 3 is driven to make the difference signals smaller, so that the image can be kept at an objective position.--.

Please substitute the paragraph starting at page 17, line 11 and ending at page 17, line 26 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

B/L6 cont  
--In the case of the first embodiment, the lens unit 3, which is arranged to be shifted in a direction perpendicular to the optical axis, is disposed closer to an image pickup surface than the variator lens unit 2. The moving amount of the image in relation to the amount of shift of the lens unit 3 comes to vary according to the position of the variator lens unit 2, i.e., according to the focal length. The amount of shift of the lens unit 3 is, therefore, decided not merely according to the optical-apparatus inclination signals obtained from the pitch angle detecting circuit 23 and the yaw angle detecting circuit 24 but is corrected also according to information on the position of the variator lens unit 2. The movement of the image due to the slant of the optical apparatus is thus arranged to be canceled by shifting the lens unit 3 in this manner.--.

Please substitute the paragraph starting at page 17, line 27 and ending at page 18, line 18 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--In the first embodiment, the aperture position of the diaphragm, which is arranged to vary the quantity of a light flux passing through the optical system, is controlled electrically to limit the full-open aperture diameter of the diaphragm according to the focal length. More specifically, the full-open aperture diameter of the diaphragm is controlled to decrease accordingly as the position of the lens system shifts from the wide-angle end position to the telephoto end position. In a case where no image-shake correcting action is required, therefore, the optical system is usable in a brighter full-open state at its telephoto

end position by removing the limitation on the full-open aperture diameter of the diaphragm. It is also possible to change the arrangement to have some auxiliary diaphragm arranged near to a main (F-number determining) diaphragm to mechanically impose the above-stated limitation on the full-open aperture diameter in a state of being interlocked with the movement of the variator lens unit 2, as will be described later herein.--.

Please substitute the paragraph starting at page 18, line 19 and ending at page 19, line 10 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

*B18 and*

--The first embodiment described above makes the image-shake correction by shifting, in a direction perpendicular to the optical axis, the third lens unit of the variable-magnification optical system composed of four lens units, which are arranged to have refractive powers in the order of positive, negative, positive and positive refractive powers. However, the type of the optical system and the lens unit to be shifted are not limited to those of the first embodiment described above. The invention is applicable also to an optical image shake correcting arrangement having a variable-angle prism within a variable-magnification optical system and also to an electronic image-shake correcting arrangement for so-called electronic image stabilization. More specifically, the invention is applicable also to an apparatus arranged to attain an image-shake-correcting effect by processing an electrical signal obtained from an image sensor, which is arranged on the image forming plane to convert an optical image into an electrical signal.--.

Please substitute the paragraph starting at page 19, line 11 and ending at page 19, line 23 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.



B16 cont

--In the first embodiment described above, a variable-magnification optical system having the image-shake correcting function is arranged to limit, according to the focal length, the full-open aperture diameter of a diaphragm, which is provided for controlling the amount of a light flux passing through the optical system. By this, a difference in luminance between the central and peripheral parts of an image plane can be lessened particularly in the neighborhood of a telephoto end position of the optical system where the difference becomes salient. Therefore, an optical apparatus can be arranged to be capable of producing high quality images according to the arrangement of the invention.--

---

Please substitute the paragraph starting at page 19, line 26 and ending at page 20, line 2 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

---

--Fig. 11 is a sectional view showing essential parts of a zoom lens (barrel) for a video camera to which the invention is applied as the second embodiment. Fig. 12 is an exploded perspective view showing in part the zoom-lens barrel shown in Fig. 11.--

B17 cont

Please substitute the paragraph starting at page 20, line 3 and ending at page 21, line 1 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--Referring to Figs. 11 and 12, a fixed tube 201 is arranged to hold a first lens unit L1. A rear tube 202 is arranged to hold a low-pass filter 203. A CCD image sensor, which is not shown, is mounted in rear of the low-pass filter 203. An image-shake correcting unit 204 is arranged to hold a third lens unit L3, which is arranged as a correction lens to be driven in a direction perpendicular to an optical axis. The image-shake correcting unit 204

is interposed in between the fixed tube 1 and the rear tube 2 and is fixed in position with screws. A second lens tube 205 is arranged to hold a second lens unit L2, which is provided for zooming. Two guide bars 206a and 206b are arranged to be supported respectively at their front and rear parts by the fixed tube 201 and the rear tube 202 and to have the second lens tube 205 movable in the direction of the optical axis. A fourth lens tube 207 is arranged to hold a fourth lens unit L4, which is provided for focus adjustment. As in the second lens tube 205, the fourth lens tube 207 is supported also by the guide bars 206a and 206b to be movable in the direction of the optical axis. The two guide bars 206a and 206b are arranged along the optical axis and on opposite sides of the optical axis not only to guide the second and fourth lens tubes 205 and 207, but also to prevent the second and fourth lens tubes 205 and 207 from turning around the optical axis.--

Please substitute the paragraph starting at page 21, line 2 and ending at page 21, line 26 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--An IG meter (IG meter unit) 208 is arranged to drive, by means of an electromagnetic actuator, diaphragm blades 803 and 804 which jointly constitute a first diaphragm means, as shown in Fig. 14. The IG meter 208 is carried jointly by the fixed tube 201 and the image-shake correcting unit 204 in a state of being interposed in between them. ND filters 806 and 807 are mounted on the front side of the diaphragm blade 803 and on the rear side of the diaphragm blade 804, respectively. The aperture diameter of the first diaphragm means is arranged to be variable according to the quantity of light incident on the CCD (sensor). Diaphragm blades 820 constitute a second diaphragm means. The second diaphragm means is composed of, in the case of the second embodiment, six diaphragm blades 820. The diameter of an aperture defined by the diaphragm blades 820 is

arranged to be variable according to the zooming position of the zoom lens, in such a manner that the quantity of on-axial light and that of off-axial light, obtained when the image-shake correcting unit 204 is driven to decenter the third lens unit L3, are balanced with each other by restricting the on-axial light flux obtained with the optical system on its telephoto side. Incidentally, the first diaphragm means is arranged to substantially determine an F-number of the zoom lens.--.

B/G  
Cone

Please substitute the paragraph starting at page 21, line 27 and ending at page 22, line 10 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--A zoom motor 209 has its driving part and its output screw part held in one body by means of a U-shaped metal plate. The zoom motor 209 is secured to the fixed tube 201 with screws. A rack 210 is mounted on the second lens tube 205. The second lens tube 205 is arranged to be driven in the direction of the optical axis with the rack 210 in a mesh state with the screw part of the zoom motor 209. In this case, any intermeshing play and any back-lash in the direction of thrust are removed by a spring 211, which is arranged to urge the rack 210 in the direction of intermeshing and in the direction of the optical axis.--.

Please substitute the paragraph starting at page 23, line 11 and ending at page 23, line 26 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

B/G  
Cone

--A photo-interrupter 215 is secured to the fixed tube 201 with a screw after it is soldered to a circuit board 216. The photo-interrupter 215 is arranged to detect the datum position of the second lens tube 205 with a light-blocking wall part 205b, which is formed

integrally with the second lens tube 205 passing through an interval between the light projecting part and the light receiving part and to allow the zoom motor 209 to move the second lens tube 205 to each zooming position according to the number of pulses inputted to the zoom motor 209. Focus adjustment is also likewise arranged to be made by detecting a light-blocking wall part 207b of the fourth lens tube 207 as a datum position with a photo-interrupter 217 and a circuit board 218, which are mounted on the rear tube 202 and by driving the focus motor 212 stepwise as necessary.--.

*B/B  
Amel*

Please substitute the paragraph starting at page 23, line 27 and ending at page 23, line 28 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--The image-shake correcting unit 204 is arranged as follows.--.

Please substitute the paragraph starting at page 24, line 1 and ending at page 24, line 11 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--Fig. 13 is an exploded perspective view of the image-shake correcting unit 204 in the second embodiment. In Fig. 13, reference numeral 240 denotes a fixed frame. The fixed frame 240 is provided with two bosses 240a (see Fig. 12) for positioning the fixed frame 240 with respect to the fixed tube 201 and two bosses 240b for positioning the fixed frame 240 with respect to the rear tube 202. The image-shake correcting unit 204 is thus carried jointly by the fixed tube 201 and the rear tube 202. A moving frame 241 is arranged to hold the third lens unit L3, which is an image-shake correction lens.--.

Please substitute the paragraph starting at page 24, line 20 and ending at page 25, line 21 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

249  
--The pins 242 and the slots 240c corresponding to them are evenly spaced at intervals of  $120^\circ$  within one and the same plane and are arranged in a balanced state to have no moment around the optical axis caused to act on the moving frame 241 by a load brought about by any sliding friction. A roll preventing plate 244 is arranged to prevent the moving frame 241 from turning around the optical axis in correcting image shaking. The roll preventing plate 244 is provided with slots 244a and 244b, which are fitted on a boss 240e provided on the fixed frame 240 and a boss, which is not shown. Other slots 244c and 244d provided also in the roll preventing plate 144 are fitted on bosses (not shown), which are provided on the moving frame 241. Hole parts 244e and 244f, which are provided in the roll preventing plate 244, allow support posts 240f and 240g formed integrally with the fixed frame 240 to pierce through these hole parts. The arrangement is such that, even if the roll preventing plate 244 moves to its maximum extent, the support posts 240f and 240g do not interfere with the roll preventing plate 244. In other words, the roll preventing plate 244 is arranged to move only in the vertical direction as viewed in Fig. 13 with respect to the fixed frame 240 while the moving frame 241 is arranged to be movable only horizontally as viewed in Fig. 13 with respect to the roll preventing plate 244. The combination of these moving directions enables the moving frame 241 to move vertically and horizontally as viewed in Fig. 13 without turning or rolling around the optical axis with respect to the fixed frame 240.--.

Please substitute the paragraph starting at page 25, line 24 and ending at page 26, line 22 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

---

*2020  
and*

--Coils 245a and 245b, which are secured to the moving frame 241, are provided for driving the moving frame 241 in the horizontal direction (hereinafter referred to as the X direction) and in the vertical direction (hereinafter referred to as the Y direction). Magnets 246a and 246b are respectively magnetized to have two poles in the X and Y directions. The magnets 246a and 246b are secured to the fixed frame 240 and fixed in position with lower yokes 247a and 247b, which are made of iron or the like arranged to attract them from behind the fixed frame 240 to cause them to be inserted respectively through hole parts 240h and 240i of the fixed frame 240. An upper yoke 248, which is made of the same material as the lower yokes 247a and 247b, is secured with screws 253 to the support posts 240f and 240g of the fixed frame 240 from its front side together with a sensor holder 249, which will be described later. The upper yoke 248 is thus arranged to form a magnetic circuit for driving in the X and Y directions. More specifically, a magnetic circuit is formed for driving in the X direction jointly by the magnet 246a, the lower yoke 247a and the upper yoke 248 with the coil 245a inserted in the magnetic circuit. Another magnetic circuit is formed for driving in the Y direction jointly by the magnet 246b, the lower yoke 247b and the upper yoke 248 with the coil 245b inserted therein. An electromagnetic actuator of the moving coil type is formed in this manner.--.

Please substitute the paragraph starting at page 26, line 23 and ending at page 27, line 16 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

Fig. 13  
--Light projecting elements 250a and 250b are IREDs or the like. Light receiving elements 251a and 251b are PSDs or the like. These elements are inserted into the sensor holder 249 from its peripheral side and are fixed in position by bonding. Narrow slits 241c and 241d, which are formed integrally with the moving frame 241, are inserted in between each of the pairs of the light-projecting and light-receiving elements. Of infrared light rays projected from the light projecting elements 251a and 251b, only the infrared rays passing through the slits 241c and 241d are received by the light receiving elements 251a and 251b. The positions of the moving frame 241 in the X and Y directions are detected by using the infrared rays thus received. The light projecting elements 250a and 250b and the light receiving elements 251a and 251b are connected to a flexible printed circuit board 252 (shown in a divided state in Fig. 13) and are thus connected to a control circuit provided on the side of a camera body, which is not shown. The wiring of the coils 245a and 245b is connected to a driving circuit, which is also disposed on the side of the camera body.--.

---

Please substitute the paragraph starting at page 27, line 19 and ending at page 28, line 15 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

---

Fig. 14  
--Fig. 14 is a plan view of the IG meter unit 208. The IG meter unit 208 includes the diaphragm blades 803 and 804, which constitute the first diaphragm means. The diaphragm blades 803 and 804 are held by a fixed frame 801 to be movable in parallel with each other in the vertical direction as viewed in Fig. 14, in a state of being guided by the bosses 801a and 801b, which are formed integrally with the fixed frame 801. Bosses 805a and 805b are provided on an arm 805 that is arranged integrally with the rotating shaft of a meter 800. The bosses 805a and 805b engage slots 803a and 804a that are provided respectively in the diaphragm blades 803 and 804. ND filters 806 and 807 are attached to


the diaphragm blades 803 and 804 by bonding. The ND filters 806 and 807 are thus arranged to reduce a light quantity to prevent the aperture diameter from becoming a predetermined aperture diameter because the quality of images deteriorates due to an adverse effect of diffraction if the aperture diameter becomes too small. To prevent the ND filters 806 and 807 from coming into sliding contact with the diaphragm blades 803 and 804, the ND filters 806 and 807 are disposed respectively in front of the diaphragm blade 803, which is located on the front side of the optical axis and in rear of the diaphragm blade 804.--.

Please substitute the paragraph starting at page 28, line 16 and ending at page 28, line 26 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--When the diaphragm blades 803 and 804 are fully opened, the ND filters 806 and 807 are in a state of being located at an optical path. The ND filters 806 and 807 come to completely cover the optical path when the aperture reaches a predetermined aperture-value position. When the aperture is further stopped down, the aperture is completely covered by the diaphragm blades 803 and 804. Further, the two upper and lower ND filters 806 and 807 are arranged to simultaneously enter the optical path to make the variation of the peripheral light quantity on the image plane uniform in correcting image shaking.--.

Please substitute the paragraph starting at page 28, line 27 and ending at page 29, line 16 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.



 --Fig. 15 shows the arrangement of the second diaphragm means in the second embodiment. In Fig. 15, reference numeral 820 denotes six blades. Each of the blades 820 is swingably carried by the fixed frame 801 with its hole part 820a engaging a boss 801c provided on the fixed frame 801. Each of the blades 820 is provided with a slot 820b that engages one of bosses 821a provided on a ring 821, which is arranged to be rotatable around the optical axis. The ring 821 has a slot 821b formed in a part extending from its periphery. The slot 821b of the ring 821 engages a boss 823a of an arm 823, which is fixedly attached to the rotating shaft of a second diaphragm driving meter 822. Therefore, the rotation torque of the meter 822 is transmitted through the arm 823 to the ring 821 to cause the ring 821 to rotate. The rotation of the ring 821 causes the six blades 820 to swing on the holes 820a in such a way as to vary the aperture diameter.--.

Please substitute the paragraph starting at page 29, line 17 and ending at page 30, line 13 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--The second diaphragm means is thus arranged to vary the diameter of an aperture according to the zooming position of the lens system irrespective of the quantity of light. In correcting image shaking, the second diaphragm means serves to alleviate variations taking place in the peripheral light quantity on the image plane. In the case of the image-shake correction by the shift method, the correction lens is disposed inside the optical system. Therefore, a peripheral light flux is determined by an optical system disposed in front of the correction lens. The quantity of peripheral light then varies when the light flux is bent by the correction lens at the time of image-shake correction. In most zoom lenses, a light flux is restricted on the side of a telephoto end by the effective diameter of a front lens. Therefore, the difference in light quantity between a central part

and a peripheral part of an image plane increases on the side of the telephoto end. In view of this, the second embodiment is arranged to appositely restrict the peripheral light flux by lessening the aperture diameter of the diaphragm accordingly as the position of the optical system shifts from its wide-angle side toward its telephoto end in such a way as to alleviate a change of the peripheral light quantity even when the correction lens is shifted.--.

Please substitute the paragraph starting at page 30, line 14 and ending at page 31, line 10 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--Figs. 16 and 17 are graphs showing the peripheral light quantity obtained by shifting the correction lens at the telephoto end. In each of these graphs, positions from the center of the image plane are shown in the horizontal direction and the quantities of light are shown in the vertical direction. Fig. 16 shows the peripheral light quantity obtained without using the second diaphragm means. Fig. 17 shows the peripheral light quantity obtained with the second diaphragm means used. In each of Figs. 16 and 17, a broken line shows a state of having the correction lens at the center of the optical axis, and a full line shows a state of having the correction lens shifted. The state of the full line and the state of the broken line are considered to appear one after another while the image-shake correction is in process. Therefore, luminance differences indicated with a reference symbol A appear one after another in the peripheral part of the image plane to give a disagreeable impression to the eye. As shown in Figs. 16 and 17, although the absolute light quantity becomes less in the case of Fig. 17 with the second diaphragm means used than in the case of Fig. 16, the change A of the peripheral light quantity, which takes place at the time of image-shake correction, can be lessened by the use of the second diaphragm means in the case of Fig. 17.--.

*BA*  
*Concl*

Please substitute the paragraph starting at page 31, line 11 and ending at page 31, line 20 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--To avoid having the peripheral light quantity unnaturally vary at the time of image-shake correction, the aperture is preferably arranged to be in a shape as close to a circle as possible. Further, in Fig. 14, a two-dot-chain line 808 represents an aperture shape of the second diaphragm means obtained in the telephoto end. The aperture is shaped in such a way as to be not affected by the ND filters 806 and 807 in the telephoto end even in a case where the diameter of the aperture 808 of the second diaphragm means is variable.--.

Please substitute the paragraph starting at page 31, line 21 and ending at page 31, line 22 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--Control over the image-shake correcting unit 204 and the diaphragm unit 208 is next described as follows.--.

---

Please substitute the paragraph starting at page 32, line 1 and ending at page 32, line 15 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

---

*BA*  
*Concl*

--The microcomputer 70 computes the amount of vibration of the camera on the basis of a detection signal obtained from the vibration sensor 71 and computes a target (or objective) position of the correction lens L3 at which image shaking, resulting from the

vibration of the camera, can be canceled. Then, according to the result of computation of the amount of movement, the coils 245a and 245b of the electromagnetic actuator are energized to drive the correction lens L3. In driving the correction lens L3, the position of the correction lens L3 is detected by correction-lens position sensors 50 and 51. The result of such detection is fed back to the microcomputer 70, so that the correction lens L3 can be accurately driven and moved to the target position computed.--.

Please substitute the paragraph starting at page 32, line 16 and ending at page 32, line 23 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--In the zoom lens, the amount of movement (the target position) of the correction lens L3 for canceling image shaking varies according to the focal length. In view of this, the number of pulses, with which the second lens unit L2 is driven, is counted to detect the focal length by a zoom position sensor 72. Then, the amount of driving of the correction lens L3 is adjusted according to the focal length detected.--.

Please substitute the paragraph starting at page 33, line 6 and ending at page 33, line 15 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--The second embodiment is arranged, as described above, to appositely restrict an on-axial light flux on the telephoto side (not restricting it on the wide-angle side) by the second diaphragm means according to the zoom position. Although the absolute quantity of light is decreased thereby, the variations taking place in the peripheral light quantity at the time of image-shake correction is effectively lessened by this arrangement, so that

B23  
ent

B23  
CML  
image shaking can be corrected without causing images to give any disagreeable impression.--.

---

Please substitute the paragraph starting at page 34, line 2 and ending at page 34, line 11 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

---

B24  
CML  
--Fig. 19 shows in a plan view the second diaphragm means in the third embodiment. In Fig. 19, reference numeral 820 indicates six blades that are arranged in the same manner as in the second embodiment. Hole parts 820a of the blades 820 engage the bosses 851c provided on the fixed frame 851, so that the blades 820 are swingably carried. The blades 820 are provided with slots 820b that engage the bosses 852a provided on the ring 852, which is arranged to be rotatable around the optical axis.--.

Please substitute the paragraph starting at page 34, line 12 and ending at page 34, line 17 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--As in the second embodiment, the third embodiment is also arranged to be capable of varying the aperture diameter by the rotation of the ring 821. In this case, however, the aperture diameter is arranged to be varied in association with the movement of the second lens tube 501, which is provided for zooming, instead of using the electromagnetic actuator.--.

Please substitute the paragraph starting at page 34, line 18 and ending at page 35, line 5 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--In Fig. 19, only the sleeve part 501a of the second lens tube 501 is illustrated.

*Box  
cont*  
The sleeve part 501a is provided with an end face cam 501b. The ring 852 has an arm part 852b extending from its periphery. The arm part 852 has an end face 852c. The rotating position of the ring 852 is restricted with the end face 852c arranged to abut on the end face cam 501b of the sleeve part 501a of the second lens tube 501. A tension coil spring 853 is attached at its one end to a hook 852d, which protrudes from the arm part 852b. The other end of the spring 853 is attached to a projection 851d provided on the fixed frame 851. The coil spring 853 is thus arranged to constantly urge the end face 852c of the ring 852 to be pushed against the end face cam 501b of the sleeve part 501a.--.

Please substitute the paragraph starting at page 35, line 14 and ending at page 35, line 18 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

*B25*  
--Since the arrangement of the third embodiment obviates the necessity of using an actuator for driving the blades, unlike in the case of the second embodiment, the third embodiment can be more simply arranged and also contributes to a reduction in electric-energy consumption.--.

Please substitute the paragraph starting at page 35, line 19 and ending at page 35, line 23 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--While the third embodiment uses a moving-coil type actuator for driving the correction lens, the same advantageous effect can be attained by replacing this actuator with a motor or an electrostrictive element or some other electromagnetic actuator.--.

1

Please substitute the paragraph starting at page 35, line 24 and ending at page 36, line 6 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

~~Ref~~  
Cont

--Further, to have an aperture shape close to a circle and laterally and vertically symmetrical, the first diaphragm of the diaphragm unit is arranged to have two parallel moving blades and two ND filters attached thereto. The second diaphragm of the diaphragm unit is arranged, also for the same purpose, to have six blades. However, according to the invention, the diaphragm unit is not limited to the arrangement disclosed. For example, both the first and second diaphragms may be arranged to be composed of six blades or to be using two swinging-type blades.--.

Please substitute the paragraph starting at page 36, line 7 and ending at page 36, line 11 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

--The arrangement of the third embodiment obviates the necessity of using an actuator for driving the second diaphragm means, so that deterioration of images at the time of image-shake correction can be minimized with simple structural arrangement.--.

Please substitute the paragraph starting at page 36, line 12 and ending at page 36, line 17 with the following replacement paragraph. A marked-up copy of this paragraph, showing the changes made thereto, is attached.

B2  
C1  
C2  
C3  
C4  
C5  
C6  
C7  
C8  
C9  
C10  
C11  
C12  
C13  
C14  
C15  
C16  
C17  
C18  
C19  
C20  
C21  
C22  
C23  
C24  
C25  
C26  
C27  
C28  
C29  
C30  
C31  
C32  
C33  
C34  
C35  
C36  
C37  
C38  
C39  
C40  
C41  
C42  
C43  
C44  
C45  
C46  
C47  
C48  
C49  
C50  
C51  
C52  
C53  
C54  
C55  
C56  
C57  
C58  
C59  
C60  
C61  
C62  
C63  
C64  
C65  
C66  
C67  
C68  
C69  
C70  
C71  
C72  
C73  
C74  
C75  
C76  
C77  
C78  
C79  
C80  
C81  
C82  
C83  
C84  
C85  
C86  
C87  
C88  
C89  
C90  
C91  
C92  
C93  
C94  
C95  
C96  
C97  
C98  
C99  
C100  
C101  
C102  
C103  
C104  
C105  
C106  
C107  
C108  
C109  
C110  
C111  
C112  
C113  
C114  
C115  
C116  
C117  
C118  
C119  
C120  
C121  
C122  
C123  
C124  
C125  
C126  
C127  
C128  
C129  
C130  
C131  
C132  
C133  
C134  
C135  
C136  
C137  
C138  
C139  
C140  
C141  
C142  
C143  
C144  
C145  
C146  
C147  
C148  
C149  
C150  
C151  
C152  
C153  
C154  
C155  
C156  
C157  
C158  
C159  
C160  
C161  
C162  
C163  
C164  
C165  
C166  
C167  
C168  
C169  
C170  
C171  
C172  
C173  
C174  
C175  
C176  
C177  
C178  
C179  
C180  
C181  
C182  
C183  
C184  
C185  
C186  
C187  
C188  
C189  
C190  
C191  
C192  
C193  
C194  
C195  
C196  
C197  
C198  
C199  
C200  
C201  
C202  
C203  
C204  
C205  
C206  
C207  
C208  
C209  
C210  
C211  
C212  
C213  
C214  
C215  
C216  
C217  
C218  
C219  
C220  
C221  
C222  
C223  
C224  
C225  
C226  
C227  
C228  
C229  
C230  
C231  
C232  
C233  
C234  
C235  
C236  
C237  
C238  
C239  
C240  
C241  
C242  
C243  
C244  
C245  
C246  
C247  
C248  
C249  
C250  
C251  
C252  
C253  
C254  
C255  
C256  
C257  
C258  
C259  
C260  
C261  
C262  
C263  
C264  
C265  
C266  
C267  
C268  
C269  
C270  
C271  
C272  
C273  
C274  
C275  
C276  
C277  
C278  
C279  
C280  
C281  
C282  
C283  
C284  
C285  
C286  
C287  
C288  
C289  
C290  
C291  
C292  
C293  
C294  
C295  
C296  
C297  
C298  
C299  
C300  
C301  
C302  
C303  
C304  
C305  
C306  
C307  
C308  
C309  
C310  
C311  
C312  
C313  
C314  
C315  
C316  
C317  
C318  
C319  
C320  
C321  
C322  
C323  
C324  
C325  
C326  
C327  
C328  
C329  
C330  
C331  
C332  
C333  
C334  
C335  
C336  
C337  
C338  
C339  
C340  
C341  
C342  
C343  
C344  
C345  
C346  
C347  
C348  
C349  
C350  
C351  
C352  
C353  
C354  
C355  
C356  
C357  
C358  
C359  
C360  
C361  
C362  
C363  
C364  
C365  
C366  
C367  
C368  
C369  
C370  
C371  
C372  
C373  
C374  
C375  
C376  
C377  
C378  
C379  
C380  
C381  
C382  
C383  
C384  
C385  
C386  
C387  
C388  
C389  
C390  
C391  
C392  
C393  
C394  
C395  
C396  
C397  
C398  
C399  
C400  
C401  
C402  
C403  
C404  
C405  
C406  
C407  
C408  
C409  
C410  
C411  
C412  
C413  
C414  
C415  
C416  
C417  
C418  
C419  
C420  
C421  
C422  
C423  
C424  
C425  
C426  
C427  
C428  
C429  
C430  
C431  
C432  
C433  
C434  
C435  
C436  
C437  
C438  
C439  
C440  
C441  
C442  
C443  
C444  
C445  
C446  
C447  
C448  
C449  
C450  
C451  
C452  
C453  
C454  
C455  
C456  
C457  
C458  
C459  
C460  
C461  
C462  
C463  
C464  
C465  
C466  
C467  
C468  
C469  
C470  
C471  
C472  
C473  
C474  
C475  
C476  
C477  
C478  
C479  
C480  
C481  
C482  
C483  
C484  
C485  
C486  
C487  
C488  
C489  
C490  
C491  
C492  
C493  
C494  
C495  
C496  
C497  
C498  
C499  
C500  
C501  
C502  
C503  
C504  
C505  
C506  
C507  
C508  
C509  
C510  
C511  
C512  
C513  
C514  
C515  
C516  
C517  
C518  
C519  
C520  
C521  
C522  
C523  
C524  
C525  
C526  
C527  
C528  
C529  
C530  
C531  
C532  
C533  
C534  
C535  
C536  
C537  
C538  
C539  
C540  
C541  
C542  
C543  
C544  
C545  
C546  
C547  
C548  
C549  
C550  
C551  
C552  
C553  
C554  
C555  
C556  
C557  
C558  
C559  
C560  
C561  
C562  
C563  
C564  
C565  
C566  
C567  
C568  
C569  
C570  
C571  
C572  
C573  
C574  
C575  
C576  
C577  
C578  
C579  
C580  
C581  
C582  
C583  
C584  
C585  
C586  
C587  
C588  
C589  
C590  
C591  
C592  
C593  
C594  
C595  
C596  
C597  
C598  
C599  
C600  
C601  
C602  
C603  
C604  
C605  
C606  
C607  
C608  
C609  
C610  
C611  
C612  
C613  
C614  
C615  
C616  
C617  
C618  
C619  
C620  
C621  
C622  
C623  
C624  
C625  
C626  
C627  
C628  
C629  
C630  
C631  
C632  
C633  
C634  
C635  
C636  
C637  
C638  
C639  
C640  
C641  
C642  
C643  
C644  
C645  
C646  
C647  
C648  
C649  
C650  
C651  
C652  
C653  
C654  
C655  
C656  
C657  
C658  
C659  
C660  
C661  
C662  
C663  
C664  
C665  
C666  
C667  
C668  
C669  
C670  
C671  
C672  
C673  
C674  
C675  
C676  
C677  
C678  
C679  
C680  
C681  
C682  
C683  
C684  
C685  
C686  
C687  
C688  
C689  
C690  
C691  
C692  
C693  
C694  
C695  
C696  
C697  
C698  
C699  
C700  
C701  
C702  
C703  
C704  
C705  
C706  
C707  
C708  
C709  
C710  
C711  
C712  
C713  
C714  
C715  
C716  
C717  
C718  
C719  
C720  
C721  
C722  
C723  
C724  
C725  
C726  
C727  
C728  
C729  
C730  
C731  
C732  
C733  
C734  
C735  
C736  
C737  
C738  
C739  
C740  
C741  
C742  
C743  
C744  
C745  
C746  
C747  
C748  
C749  
C750  
C751  
C752  
C753  
C754  
C755  
C756  
C757  
C758  
C759  
C760  
C761  
C762  
C763  
C764  
C765  
C766  
C767  
C768  
C769  
C770  
C771  
C772  
C773  
C774  
C775  
C776  
C777  
C778  
C779  
C780  
C781  
C782  
C783  
C784  
C785  
C786  
C787  
C788  
C789  
C790  
C791  
C792  
C793  
C794  
C795  
C796  
C797  
C798  
C799  
C800  
C801  
C802  
C803  
C804  
C805  
C806  
C807  
C808  
C809  
C810  
C811  
C812  
C813  
C814  
C815  
C816  
C817  
C818  
C819  
C820  
C821  
C822  
C823  
C824  
C825  
C826  
C827  
C828  
C829  
C830  
C831  
C832  
C833  
C834  
C835  
C836  
C837  
C838  
C839  
C840  
C841  
C842  
C843  
C844  
C845  
C846  
C847  
C848  
C849  
C850  
C851  
C852  
C853  
C854  
C855  
C856  
C857  
C858  
C859  
C860  
C861  
C862  
C863  
C864  
C865  
C866  
C867  
C868  
C869  
C870  
C871  
C872  
C873  
C874  
C875  
C876  
C877  
C878  
C879  
C880  
C881  
C882  
C883  
C884  
C885  
C886  
C887  
C888  
C889  
C890  
C891  
C892  
C893  
C894  
C895  
C896  
C897  
C898  
C899  
C900  
C901  
C902  
C903  
C904  
C905  
C906  
C907  
C908  
C909  
C910  
C911  
C912  
C913  
C914  
C915  
C916  
C917  
C918  
C919  
C920  
C921  
C922  
C923  
C924  
C925  
C926  
C927  
C928  
C929  
C930  
C931  
C932  
C933  
C934  
C935  
C936  
C937  
C938  
C939  
C940  
C941  
C942  
C943  
C944  
C945  
C946  
C947  
C948  
C949  
C950  
C951  
C952  
C953  
C954  
C955  
C956  
C957  
C958  
C959  
C960  
C961  
C962  
C963  
C964  
C965  
C966  
C967  
C968  
C969  
C970  
C971  
C972  
C973  
C974  
C975  
C976  
C977  
C978  
C979  
C980  
C981  
C982  
C983  
C984  
C985  
C986  
C987  
C988  
C989  
C990  
C991  
C992  
C993  
C994  
C995  
C996  
C997  
C998  
C999  
C1000  
C1001  
C1002  
C1003  
C1004  
C1005  
C1006  
C1007  
C1008  
C1009  
C1010  
C1011  
C1012  
C1013  
C1014  
C1015  
C1016  
C1017  
C1018  
C1019  
C1020  
C1021  
C1022  
C1023  
C1024  
C1025  
C1026  
C1027  
C1028  
C1029  
C1030  
C1031  
C1032  
C1033  
C1034  
C1035  
C1036  
C1037  
C1038  
C1039  
C1040  
C1041  
C1042  
C1043  
C1044  
C1045  
C1046  
C1047  
C1048  
C1049  
C1050  
C1051  
C1052  
C1053  
C1054  
C1055  
C1056  
C1057  
C1058  
C1059  
C1060  
C1061  
C1062  
C1063  
C1064  
C1065  
C1066  
C1067  
C1068  
C1069  
C1070  
C1071  
C1072  
C1073  
C1074  
C1075  
C1076  
C1077  
C1078  
C1079  
C1080  
C1081  
C1082  
C1083  
C1084  
C1085  
C1086  
C1087  
C1088  
C1089  
C1090  
C1091  
C1092  
C1093  
C1094  
C1095  
C1096  
C1097  
C1098  
C1099  
C1100  
C1101  
C1102  
C1103  
C1104  
C1105  
C1106  
C1107  
C1108  
C1109  
C1110  
C1111  
C1112  
C1113  
C1114  
C1115  
C1116  
C1117  
C1118  
C1119  
C1120  
C1121  
C1122  
C1123  
C1124  
C1125  
C1126  
C1127  
C1128  
C1129  
C1130  
C1131  
C1132  
C1133  
C1134  
C1135  
C1136  
C1137  
C1138  
C1139  
C1140  
C1141  
C1142  
C1143  
C1144  
C1145  
C1146  
C1147  
C1148  
C1149  
C1150  
C1151  
C1152  
C1153  
C1154  
C1155  
C1156  
C1157  
C1158  
C1159  
C1160  
C1161  
C1162  
C1163  
C1164  
C1165  
C1166  
C1167  
C1168  
C1169  
C1170  
C1171  
C1172  
C1173  
C1174  
C1175  
C1176  
C1177  
C1178  
C1179  
C1180  
C1181  
C1182  
C1183  
C1184  
C1185  
C1186  
C1187  
C1188  
C1189  
C1190  
C1191  
C1192  
C1193  
C1194  
C1195  
C1196  
C1197  
C1198  
C1199  
C1200  
C1201  
C1202  
C1203  
C1204  
C1205  
C1206  
C1207  
C1208  
C1209  
C1210  
C1211  
C1212  
C1213  
C1214  
C1215  
C1216  
C1217  
C1218  
C1219  
C1220  
C1221  
C1222  
C1223  
C1224  
C1225  
C1226  
C1227  
C1228  
C1229  
C1230  
C1231  
C1232  
C1233  
C1234  
C1235  
C1236  
C1237  
C1238  
C1239  
C1240  
C1241  
C1242  
C1243  
C1244  
C1245  
C1246  
C1247  
C1248  
C1249  
C1250  
C1251  
C1252  
C1253  
C1254  
C1255  
C1256  
C1257  
C1258  
C1259  
C1260  
C1261  
C1262  
C1263  
C1264  
C1265  
C1266  
C1267  
C1268  
C1269  
C1270  
C1271  
C1272  
C1273  
C1274  
C1275  
C1276  
C1277  
C1278  
C1279  
C1280  
C1281  
C1282  
C1283  
C1284  
C1285  
C1286  
C1287  
C1288  
C1289  
C1290  
C1291  
C1292  
C1293  
C1294  
C1295  
C1296  
C1297  
C1298  
C1299  
C1300  
C1301  
C1302  
C1303  
C1304  
C1305  
C1306  
C1307  
C1308  
C1309  
C1310  
C1311  
C1312  
C1313  
C1314  
C1315  
C1316  
C1317  
C1318  
C1319  
C1320  
C1321  
C1322  
C1323  
C1324  
C1325  
C1326  
C1327  
C1328  
C1329  
C1330  
C1331  
C1332  
C1333  
C1334  
C1335  
C1336  
C1337  
C1338  
C1339  
C1340  
C1341  
C1342  
C1343  
C1344  
C1345  
C1346  
C1347  
C1348  
C1349  
C1350  
C1351  
C1352  
C1353  
C1354  
C1355  
C1356  
C1357  
C1358  
C1359  
C1360  
C1361  
C1362  
C1363  
C1364  
C1365  
C1366  
C1367  
C1368  
C1369  
C1370  
C1371  
C1372  
C1373  
C1374  
C1375  
C1376  
C1377  
C1378  
C1379  
C1380  
C1381  
C1382  
C1383  
C1384  
C1385  
C1386  
C1387  
C1388  
C1389  
C1390  
C1391  
C1392  
C1393  
C1394  
C1395  
C1396  
C1397  
C1398  
C1399  
C1400  
C1401  
C1402  
C1403  
C1404  
C1405  
C1406  
C1407  
C1408  
C1409  
C1410  
C1411  
C1412  
C1413  
C1414  
C1415  
C1416  
C1417  
C1418  
C1419  
C1420  
C1421  
C1422  
C1423  
C1424  
C1425  
C1426  
C1427  
C1428  
C1429  
C1430  
C1431  
C1432  
C1433  
C1434  
C1435  
C1436  
C1437  
C1438  
C1439  
C1440  
C1441  
C1442  
C1443  
C1444  
C1445  
C1446  
C1447  
C1448  
C1449  
C1450  
C1451  
C1452  
C1453  
C1454  
C1455  
C1456  
C1457  
C1458  
C1459  
C1460  
C1461  
C1462  
C1463  
C1464  
C1465  
C1466  
C1467  
C1468  
C1469  
C1470  
C1471  
C1472  
C1473  
C1474  
C1475  
C1476  
C1477  
C1478  
C1479  
C1480  
C1481  
C1482  
C1483  
C1484  
C1485  
C1486  
C1487  
C1488  
C1489  
C1490  
C1491  
C1492  
C1493  
C1494  
C1495  
C1496  
C1497  
C1498  
C1499  
C1500  
C1501  
C1502  
C1503  
C1504  
C1505  
C1506  
C1507  
C1508  
C1509  
C1510  
C1511  
C1512  
C1513  
C1514  
C1515  
C1516  
C1517  
C1518  
C1519  
C1520  
C1521  
C1522  
C1523  
C1524  
C1525  
C1526  
C1527  
C1528  
C1529  
C1530  
C1531  
C1532  
C1533  
C1534  
C1535  
C1536  
C1537  
C1538  
C1539  
C1540  
C1541  
C1542  
C1543  
C1544  
C1545  
C1546  
C1547  
C1548  
C1549  
C1550  
C1551  
C1552  
C1553  
C1554  
C1555  
C1556  
C1557  
C1558  
C1559  
C1560  
C1561  
C1562  
C1563  
C1564  
C1565  
C1566  
C1567  
C1568  
C1569  
C1570  
C1571  
C1572  
C1573  
C1574  
C1575  
C1576  
C1577  
C1578  
C1579  
C1580  
C1581  
C1582  
C1583  
C1584  
C1585  
C1586  
C1587  
C1588  
C1589  
C1590  
C1591  
C1592  
C1593  
C1594  
C1595  
C1596  
C1597  
C1598  
C1599  
C1600  
C1601  
C1602  
C1603  
C1604  
C1605  
C1606  
C1607  
C1608  
C1609  
C1610  
C1611  
C1612  
C1613  
C1614  
C1615  
C1616  
C1617  
C1618  
C1619  
C1620  
C1621  
C1622  
C1623  
C1624  
C1625  
C1626  
C1627  
C1628  
C1629  
C1630  
C1631  
C1632  
C1633  
C1634  
C1635  
C1636  
C1637  
C1638  
C1639  
C1640  
C1641  
C1642  
C1643  
C1644  
C1645  
C1646  
C1647  
C1648  
C1649  
C1650  
C1651  
C1652  
C1653  
C1654  
C1655  
C1656  
C1657  
C1658  
C1659  
C1660  
C1661  
C1662  
C1663  
C1664  
C1665  
C1666  
C1667  
C1668  
C1669  
C1670  
C1671  
C1672  
C1673  
C1674  
C1675  
C1676  
C1677  
C1678  
C1679  
C1680  
C1681  
C1682  
C1683  
C1684  
C1685  
C1686  
C1687  
C1688  
C1689  
C1690  
C1691  
C1692  
C1693  
C1694  
C1695  
C1696  
C1697  
C1698  
C1699  
C1700  
C1701  
C1702  
C1703  
C1704  
C1705  
C1706  
C1707  
C1708  
C1709  
C1710  
C1711  
C1712  
C1713  
C1714  
C1715  
C1716  
C1717  
C1718  
C1719  
C1720  
C1721  
C1722  
C1723  
C1724  
C1725  
C1726  
C1727  
C1728  
C1729  
C1730  
C1731  
C1732  
C1733  
C1734  
C1735  
C1736  
C1737  
C1738  
C1739  
C1740  
C1741  
C1742  
C1743  
C1744  
C1745  
C1746  
C1747  
C1748  
C1749  
C1750  
C1751  
C1752  
C1753  
C1754  
C1755  
C1756  
C1757  
C1758  
C1759  
C1760  
C1761  
C1762  
C1763  
C1764  
C1765  
C1766  
C1767  
C1768  
C1769  
C1770  
C1771  
C1772  
C1773  
C1774  
C1775  
C1776  
C1777  
C1778  
C1779  
C1780  
C1781  
C1782  
C1783  
C1784  
C1785  
C1786  
C1787  
C1788  
C1789  
C1790  
C1791  
C1792  
C1793  
C1794  
C1795  
C1796  
C1797  
C1798  
C1799  
C1800  
C1801  
C1802  
C1803  
C1804  
C1805  
C1806  
C1807  
C1808  
C1809  
C1810  
C1811  
C1812  
C1813  
C1814  
C1815  
C1816  
C1817  
C1818  
C1819  
C1820  
C1821  
C1822  
C1823  
C1824  
C1825  
C1826  
C1827  
C1828  
C1829  
C1830  
C1831  
C1832  
C1833  
C1834  
C1835  
C1836  
C1837  
C1838  
C1839  
C1840  
C1841  
C1842  
C1843  
C1844  
C1845  
C1846  
C1847  
C1848  
C1849  
C1850  
C1851  
C1852  
C1853  
C1854  
C1855  
C1856  
C1857  
C1858  
C1859  
C1860  
C1861  
C1862  
C1863  
C1864  
C1865  
C1866  
C1867  
C1868  
C1869  
C1870  
C1871  
C1872  
C1873  
C1874  
C1875  
C1876  
C1877  
C1878  
C1879  
C1880  
C1881  
C1882  
C1883  
C1884  
C1885  
C1886  
C1887  
C1888  
C1889  
C1890  
C1891  
C1892  
C1893  
C1894  
C1895  
C1896  
C1897  
C1898  
C1899  
C1900  
C1901  
C1902  
C1903  
C1904  
C1905  
C1906  
C1907  
C1908  
C1909  
C1910  
C1911  
C